



2010 43QGP Allegro Bus

2/8/2011

FIRST modification **INSTALL ADDITIONAL VENTILATED SHELVING**. Install in PS living-room cabinet and the PS hanging closet. The ventilated shelving was purchased from our local Lowe's, we found the six foot long 12 inch shelving was a exact fit in the over PS sofa cabinet. Our cabinet has six doors which make access easy for installing the new shelf. Two hardwood shelf supports were installed, one on each end. The shelf when installed would split the height of the seventeen (17) inch tall cabinet making the new top shelf about eight (8) inches while the bottom portion would also have about eight (8) inches. The shelving was installed with the shelf lip up to prevent items on the top shelf from sliding off. We found the best way to install the shelf was to remove the cabinet door nearest the kitchen. Once it was removed the shelf can be slid into position and laid down on the new shelf supports. To keep the shelf tight against the cabinet back wall and prevent the shelf sliding away from the back wall we installed two two-hole cabinet clips with screws, one close to each end. That also allows the front edge of the new shelving to be lifted making it easier to add or remove objects from the lower shelf.



The second shelving addition was to the bedroom closet. Tiffin installed the electrical circuit breaker panel on the floor on the passenger side of the hanging closet. Since about 16 inches of the hanging length had been compromised we decided to install two 16 inch deep shelves in that corner over the electrical panel. Four hardwood shelf supports were cut and installed in order to support the new shelves. Take care to insure the forward wall depth will support the screw length you are using before installing the screws for the left end shelf support, or the screws may protrude through the wall into the bathroom.



After installation the lower shelf is mounted six (6) inches above the wooden top of the electrical panel. The distance between shelves is thirteen (13) inches and the top shelf is about fourteen (14) inches below the closet's top wooden shelf.

All shelving after they were cut had rubber caps installed to prevent damage to the adjacent wallpaper. Again these shelves were secured to the wall behind the shelf to prevent the shelf from sliding away from the wall and also allow the front of the new shelf to be lifted making storing or removal of stored items easier.