

MANUAL **START/STOP** MENU

Set Idle: Defeat	Set Idle: 20W load	Set Idle: 30W load	Set Idle: 40W load	Set Idle: 50W load				
Bat Capacity: Auto	Bat Capacity: 125 A-hrs	Bat Capacity: 250 A-hrs	Bat Capacity: 375 A-hrs	Bat Capacity: 500 A-hrs	Bat Capacity: 1000 A-hrs			
Battery Type: GEL Cell	Battery Type: Flooded Lead	Battery Type: AGM						
Charge Rate: 100% of Max	Charge Rate: 90% of Max	Charge Rate: 80% of Max	----- ➔	Charge Rate: 20% of Max	Charge Rate: 10% of Max			
Shore Power 30 A or More	Shore Power 25 Amps	Shore Power 20 Amps	Shore Power 15 Amps	Shore Power 10 Amps	Shore Power 5 Amps			
Remote Setup: Last Key	Remote Setup: Power Saver	Remote Setup: Rolling Display						
LCD Contrast Max Contrast	LCD Contrast 87%	LCD Contrast 62%	----- ➔		LCD Contrast Min Contrast			
Generator Start: Manual (PUSH ON)	Generator Start: Auto @ 11.0 V	Generator Start: Auto @ 11.5 V	Generator Start: Auto @ 11.8 V	Generator Start: Auto @ 12.0 V	Generator Start: Auto @ 12.2 V			
Generator Stop: Manual (PUSH OFF)	Generator Stop: Auto @ Absorb	Generator Stop: Auto @ Float						
Gen Start/Stop: Therm Disabled	Gen Start/Stop: Therm Enabled							
Begin Gen Quiet 0:00	Setting the Begin and End Quiet time the same DISABLES the Quiet time.							
End Gen Quite 0:00								
Select Genset: Onan Quiet Diesel	Select Genset: PowerTech Diesel	Select Genset: Generac Diesel						
Set Clk: 0-23:59 00:00								

2007 Phaeton 40QSH, Xantrex RC/GS Version 2.0